

Versatile and accurate: the new KASTOcut D 4.

Precision and efficiency

- Infinitely adjustable mitre cuts by means of easy to turn saw unit.
- Large mitre range from + 60° to - 45°
- Electronic digital display of the mitre angle
- Point of the saw unit is located at the cutting point of saw blade and material support edge, therefore no length adjustment due to change of mitre angle will be necessary.
- Upon request: Infinitely adjustable saw blade speed from 20 up to 110 m/min.
- Constant material feeds or constant cutting power by means of KASTO-universal hydraulic, no change of saw blade is necessary.
- Heavy-duty, distortion -free welded construction and frequency-controlled main drive ensure a quiet, vibration-free operation.



Technical Data KASTOcut

D 4

Cutting range,	400 mm (1' 3 3/4")
Cutting range, flat (HxW)	400 x 320 mm (1' 3 3/4" x 1' 19/32")
At 45° mitre cutting	320 mm / 320 x 320 (1' 19/32")
At 60° mitre cutting	240 mm/ 210 x 320 mm (9 29/64" / 8 17/64" x 1' 19/32")
Shortest length of residual piece	35 mm (1 3/8")
Smallest diameter to be cut	6 mm (15/65")
Mitre cutting range	+ 60° up to -45°
Saw blade speed, pole changing	32 / 64 m/min (105 / 210 ft/min)
Saw blade speed, infinitely adjustable (accessory)	20 – 110 m/min (65,6 – 360,9 ft/min)
Total power	3,5 kW
Power of saw motor	1,7 kW
Dimensions of saw blade	5090 x 34 x 1,1 mm / (16' 8 25/64" x 1 21/64" x 1/32")
Overall dimensions (LxWxH)	1240 x 2700 x 1369 mm (4' 13/16" x 8' 10 19/64" x 4' 5 57/64")
Total weight	920 kg (2031 lbs)

KASTO
Maschinenbau GmbH & Co. KG
Industriestr. 14
77855 Achern/Deutschland
Telefon +49(0)78 41/61-0
Telefax +49(0)78 41/61-355
e-mail kasto@kasto.de
Internet <http://www.kasto.de>

KASTO: universal Bandsawing Machine for Mitre Cutting
with mitre cutting adjustment on both sides

