

## SERIE 7000



### CONNECTOR SLEEVES SINGLE IN BRASS

| <i>TYPE-NO.:</i> | <i>DESCRIPTION:</i> | <i>DIAM.:</i>       | <i>THREAD:</i>         |
|------------------|---------------------|---------------------|------------------------|
| 7130             | 1 union for plane   | 3/8" tube and BSP   | 3/8" internal thread   |
| 7131             | 1 union for plane   | 1/2" tube and BSP   | 1/2" internal thread   |
| 7133             | 1 union for plane   | 3/4" tube und BSP   | 3/4" internal thread   |
| 7134             | 1 union for plane   | 1" tube and BSP     | 1" internal thread     |
| 7135             | 1 union for plane   | 1 1/4" tube and BSP | 1 1/4" internal thread |
| 7136             | 1 union for plane   | 1 1/2" tube and BSP | 1 1/2" internal thread |
| 7138             | 1 union for plane   | 2" tube and BSP     | 2" internal thread     |



### CONNECTOR SLEEVES DOUBLE IN BRASS

|      |                    |              |
|------|--------------------|--------------|
| 7311 | 2 unions for plane | 1/2" tubes   |
| 7313 | 2 unions for plane | 3/4" tubes   |
| 7314 | 2 unions for plane | 1" tubes     |
| 7315 | 2 unions for plane | 1 1/4" tubes |
| 7316 | 2 unions for plane | 1 1/2" tubes |

---

### HIGHEST PRESSURE 45 BAR

#### *Materials:*

|                  |                      |
|------------------|----------------------|
| Body             | Brass (CuZn39Pb3)    |
| Union            | Brass (CuZn39Pb3)    |
| Compression ring | Stainless steel 18/8 |
| Slide ring       | Stainless steel 18/8 |
| Washer           | E P D M rubber       |

---

E P D M rubber is temperature resistant from +40° up to and incl. +140° C.  
Resistant to air, water, steam, base, acids, alcohol etc. Is resistant to maturing and ozone.

E P D M is **not** resistant to mineral oils and fatty acids. At lubrication oils/grease on silicone basis shall be used.